




Stage , 3V50 Cats



Stage , 3V50 Cats

Content: 70% Vinyl, 30% Polyester

Width: 54"

Weight: 30 oz./linear yard

Backing: 70% Vinyl Face, 30% Polyester Backing

Finish: SILVERGUARD and PERMABLOK

Repeat: None

Directional: Yes

Railroaded: No

Abrasion: 930,000 Double Rubs

Breaking Strength: Warp 121 lbs. / Fill 72 lbs.

Crocking: Dry Class 4 / Wet Class 4

Lightfastness: 1000 hours

Flammability: Passes Cal 117-2013; NFPA 260/UFAC Class 1; Cal 117 Section E; Boston Fire Dept. Code (BFD IX-1); FAA/FAR 25.853(a) & Appendix F Part I(a)(ii); FMVSS 302; IMO A.652 (16) 8.2 & 8.3; NFPA 701 (small scale); NY/NJ Port Authority; Fed. St.

191A M 5903; ASTM E662.1; May comply with Cal. Tech. Bul. 133 when combined with appropriate components.:

Cleaning Code: WS, BC

Lead Time

Fabric Disclaimer Monitors and display settings vary widely between computers. As a result, all fabric colors shown here are approximate and subject to variance from the actual color on physical chairs. For more accurate ideas of color tones, etc. please contact your favorite OM representative to obtain a sample or fabric swatch.

